



Ningbo Longlive was founded in 1980, covering an area of 30,000 square meters. We are specialized in manufacturing brass fittings and valves, exported to Europe, America, South America, Australia, Japan, Dubai, etc. There is the whole set of equipment of forging, stamping, casting, machining, polishing, plating, PVD and testing machines.

Since 2008 Longlive has been focusing on LEAD FREE products due to California State Law AB1953. We can produce



Spectrographic analysis



Roughness Comparison



Laser



Salt spray test



SPECIAL THREAD CMC MACHINE



Three coordinate measuring



Screw gauge



Hardness Tester



Thickness gauge



Vernier Caliper



Gauge

Brass Geka Quick Coupling



Technical Features

Threadings ISO228/1

Max inlet pressure 6 bar

Working temperature -30°C-60°C

Construction

Body in brass UNI EN 12165-CW617/N

"Quick" washer in EPDM Sh. A 60 ±5 silicone

Female fitting washer in NBR



LL-40001



LL-40002



LL-40003



LL-40004



LL-40005



LL-40006



LL-40007



LL-40008



LL-40009



LL-40010



LL-40011



LL-40012



Brass Camlock

Type A: Male adapter x female thread

Size: 1/2"-6"



Brass Camlock

Type E: Male adapter x hose shank

Size: 1/2"-6"

Brass Camlock

Type B: Female coupler x male thread

Size: 1/2"-6"



Brass Camlock

Type F: Male adapter x male thread

Size: 1/2"-6"

Brass Camlock

Type C: Female coupler x hose shank

Size: 1/2"-6"



Brass Camlock

Type DC: Dust cap

Size: 1/2"-6"



Brass Camlock

Type DP: Dust plug

Size: 1/2"-6"

Brass Camlock

Type D: Female coupler x female thread

Size: 1/2"-6"





SS Camlock

Type A: Male adapter x female thread

Size: 1/2"-10"



SS Camlock


Type E: Male adapter x hose shank

Size: 1/2"-10"

SS Camlock

Type B: Female coupler x male thread

Size: 1/2"-10"



SS Camlock

Type F: Male adapter x male thread

Size: 1/2"-10"

SS Camlock

Type C: Male coupler x hose shank

Size: 1/2"-10"



SS Camlock

Type DC: Dust cap

Size: 1/2"-10"



SS Camlock

Type D: Female coupler x female thread

Size: 1/2"-10"



SS Camlock

Type DP: Dust plug

Size: 1/2"-10"



Aluminum Camlock

Type A: Male adapter x female thread

Size: 1/2"-8"



Aluminum Camlock

Type E: Male adapter x hose shank

Size: 1/2"-8"



Aluminum Camlock

Type B: Female Coupler x male thread

Size: 1/2"-8"

Aluminum Camlock

Type F: Male adapter x male thread

Size: 1/2"-8"



Aluminum Camlock

Type C: Female coupler x hose shank

Size: 1/2"-8"



Aluminum Camlock

Type DC: Dust cap

Size: 1/2"-8"



Aluminum Camlock

Type D: Female coupler x female thread

Size: 1/2"-8"

Aluminum Camlock

Type DP: Dust plug

Size: 1/2"-8"





PP Camlock

Type A: Male adapter x female thread

Size: 1/2"-4"



PP Camlock

Type E: Male adapter x hose shank

Size: 1/2"-4"

PP Camlock

Type B: Female coupler x male thread

Size: 1/2"-4"



PP Camlock

Type C: Female coupler x hose shank

Size: 1/2"-4"



PP Camlock

Type D: Female coupler x female thread

Size: 1/2"-4"



PP Camlock

Type F: Male adapter x male thread

Size: 1/2"-4"

PP Camlock

Type DC: Dust cap

Size: 1/2"-4"



PP Camlock

Type DP: Dust plug

Size: 1/2"-4"



Nylon Camlock

Type A: Male adapter x female thread

Size: 1/2"-4"



Nylon Camlock

Type E: Male adapter x hose shank

Size: 1/2"-4"



Nylon Camlock

Type B: Female Coupler x male thread

Size: 1/2"-4"

Nylon Camlock

Type F: Male adapter x male thread

Size: 1/2"-4"



Nylon Camlock

Type C: Female Coupler x hose shank

Size: 1/2"-4"



Nylon Camlock

Type DC: Dust cap

Size: 1/2"-4"



Nylon Camlock

Type D: Female Coupler x female thread

Size: 1/2"-4"

Nylon Camlock

Type DP: Dust plug

Size: 1/2"-4"

